



## **SD45170F – 170L Flammable Cabinet (Self-Closing)**

Double-wall construction with 38mm insulating air space for fire resistance. Over 1.2mm thick, fully welded, construction holds squareness for longer life, offering greater protection in a fire with 5.3cm leak tight sump at the bottom of cabinet's maximally catching incidental drips.

Door can be fully opened to 180°, easy to operate, three-point latch with a manual lock for better security. Standardized warning label is highly visible and anti-corrosive.

Unique spill-catcher shelves catch incidental drips and adjust on 6cm centers. Durable chemical resistant, lead-free powder coat inside and outside cabinet, reduce effects of corrosion and humidity. 2" vents with integral flame arresters in both sides of every cabinet.

In terms of OSHA, there is a built-in grounding static connector for easy grounding, on outside side panel.



<b>Size (External)</b>	1090 W x 1650 H x 460 D (mm)
<b>Size (Packing)</b>	1200 W x 1820 H x 570 D (mm)
<b>Material Specifications</b>	18 Ga Steel
<b>Capacity</b>	170L
<b>Doors / Shelves</b>	2 Doors (self-closing) / 2 adj. shelf
<b>Color</b>	Yellow
<b>Approvals</b>	FM
<b>Compliance</b>	OSHA