







AC 900/50 CM Flammable Cabinet - Type 90min

TÜV CERTIFICATION. Extra inflatable trimming with protection against "Cold and Hot fumes" and dusts. Self-closing doors with automatic return at every opening. Safety closing system: in case of fire, automatically closes the doors at a temperature of >50° C. Not electric. Natural internal ventilation system for vapours, equipped with two certified security valves for air recycling with automatic closure at $70 \pm 10^\circ$ C. The valves are positioned at the top and at the bottom of the rear wall of the cabinet in order to grant the release of substances, as per normative. External connection collar \emptyset 100 mm. 3 shelves adjustable in height made of electrogalvanized steel painted with epoxy acidproof coatings. Tray-shaped shelves to collect any liquid spillage of breakages. Removable and adjustable shelves with anti-falling security lock by rack. Collection capacity of the shelf approx. 7 litres, loading capacity 80kg. Watertight bottom basin in electrogalvanized steel painted with epoxy anti-acid coatings. Certified palletized base: new design of the base for easier transportation of the cabinet with removable cover.

Size (External)	895 x 510 x 600/620 h (mm)		
Size (Internal)	730 x 355 x 440 h (mm)		
Weight	145kg		
Capacity	25L		
Shelf Capacity	80kg		
Colour	Yellow		
Approvals	TÜV CERTIFICATION		
Compliance	EN 14470-1, EN 16121, EN 16122		